

ART. #	Type	Description	Prix Client CAD
20081370	EPM 6-30-EN54	Emergency Power Supply Manager according EN54-4, 6 Outputs with 30A each, 1438/CPD/0322	1 302,00 \$
20122649	DA 10-130/T-EN54	Directional speaker, 10 watts, RAL 9010, aluminium, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP65, 1438/CPR/0234	158,20 \$
20122650	DA 10-260/T-EN54	Bi-directional speaker, 10 watts, RAL 9010, aluminium, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP65, 1438/CPR/0234	169,40 \$
20102185	DA-S 20-130/T-EN54	Soundprojector, 20 watts, RAL 9010, aluminium, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP65, 1438/CPR/0234	163,80 \$
20173235	DA-P 10-260/T-EN54	Bi-directional speaker, 10 watts, ABS, RAL9016, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP56, 1438/CPR/xxxx	78,40 \$
20142815	DA-P 20-130/T-EN54	Soundprojector, 20 watts, ABS, white, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP56, 1438/CPR/0388	92,40 \$
20102186	DK 10/T-EN54	Horn speaker, 10 watts (100V & 20ohms), RAL 7035, ABS, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP66, 1438/CPR/0242	95,20 \$
20102187	DK 15/T-EN54	Horn speaker, 15 watts (100V & 20ohms), RAL 7035, ABS, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP66, 1438/CPR/0242	109,20 \$
20102188	DK 30/T-EN54	Horn speaker, 30 watts (100V & 20ohms), RAL 7035, ABS, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP66, 1438/CPR/0242	142,80 \$
20102232	DK-MH 30/T plus-EN54	Music horn, 2-way-system, 30 watts, RAL 7035, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP66, 1438/CPR/0242	291,20 \$
20153015	TH-100-EN54	Boundary horn speaker for Voice Alarm, 100W, RAL 7023, ABS, certified EN 54-24, BS 5839 compliant, IP66, 1438/CPR/0481	2 688,00 \$
20163071	TH-100-WH	TH-100 mounting brackets, 4 pieces, made of V5A stainless steel	156,80 \$
20163069	TH-100-PH	TH-100 premium mounting kit, made of V5A stainless steel	261,80 \$
20122608	EN 54-24 Sicherheitsset	Ceramic block and thermal fuse - assembled	14,00 \$
20142906	DL 06-77/T-EN54	Ceiling speaker, 6 watts, RAL 9016, metal, with thermal fuse, certified EN 54-24, IP21C, 1438/CPR/0434	46,20 \$
20132652	DL-E 06-130/T-EN54	Ceiling speaker, 6 watts, RAL 9016, metal, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPR/0347	47,60 \$
20132652S	DL-E 06-130/T-EN54 safe	Ceiling speaker, 6 watts, RAL 9016, metal, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPR/0347	57,40 \$
20132662	FE 130-EN54	Metal fire dome for DL-E 06-130/T-EN54, 1438/CPR/0347	18,20 \$
20132653	DL-E 06-165/T-EN54	Ceiling speaker, 6 watts, RAL 9016, metal, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPR/0347	50,40 \$
20132653S	DL-E 06-165/T-EN54 safe	Ceiling speaker, 6 watts, RAL 9016, metal, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPR/0347	58,80 \$
20132739	FE 165-EN54	Metal fire dome for DL-E 06-165/T-EN54, 1438/CPR/0347	19,60 \$
20102189	DL 06-130/T-EN54	Ceiling speaker, 6 watts, RAL 9010, metal, with thermal fuse and ceramic block, firedome, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPR/0233	50,40 \$
20173196	DL-SE 06-130/T-EN54	Ceiling speaker, 6 watts, RAL 9016, metal, with firedome and WAGO-connector 221, certified EN 54-24, IP21C, 1438/CPR/xxxx	39,20 \$
20173325	DL-SQ 06-130/T-EN54	Square design ceiling speaker, 6 watts, RAL 9016, metal, with firedome and WAGO-connector 221, certified EN 54-24, IP21C, 1438/CPR/xxxx	43,40 \$
20102191	DL 06-165/T-EN54	Ceiling speaker, 6 watts, RAL 9010, metal, with thermal fuse and ceramic block, firedome, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPR/0233	53,20 \$
20173197	DL-SE 06-165/T-EN54	Ceiling speaker, 6 watts, RAL 9016, metal, with firedome and WAGO-connector 221, certified EN 54-24, IP21C, 1438/CPR/xxxx	40,60 \$
20142814	DL-FF 06-165/T-EN54	Ceiling speaker, 6 watts, RAL 9010, metal, with thermal fuse and ceramic block, firedome, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPR/0384	68,60 \$
20142899	DL 06-200/T-EN54	Ceiling speaker, 6 watts, RAL 9010, metal, with thermal fuse and ceramic block, firedome, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPR/0233	74,20 \$
20142907	DL-E 10-165/T-EN54 safe	Ceiling speaker, 10 watts, RAL 9016, metal, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPR/0347	103,60 \$
20142908	DL-SF 06-100/T-EN54	Ceiling speaker, 6 watts (100V & 8ohms), RAL 9016, ABS (UL 94-V0), with thermal fuse and ceramic block, certified EN 54-24, IP54, 1438/CPR/0426	61,60 \$
20142900	DL 10-165/T-EN54	Ceiling speaker, 10 watts, RAL 9010, metal, with thermal fuse and ceramic block, firedome, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPR/0233	67,20 \$
20102192	DL 10-200/T-EN54	Ceiling speaker, 10 watts, RAL 9010, metal, with thermal fuse and ceramic block, firedome, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPR/0233	71,40 \$
20102190	DL 20-130/T-EN54	Ceiling speaker, 20 watts, RAL 9010, metal, with thermal fuse and ceramic block, firedome, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPR/0233	103,60 \$
20142898	DL 20-200/T-EN54	Ceiling speaker, 20 watts, RAL 9010, metal, with thermal fuse and ceramic block, firedome, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPR/0233	110,60 \$
20142897	DL 06-130/T plus-EN54	Ceiling speaker, 2-way-system, 6 watts, RAL 9010, metal, with thermal fuse and ceramic block, firedome, certified EN 54-24, BS 5839 compliant, IP21C 1438/CPR/0233	72,80 \$
20102193	DL 10-165/T plus-EN54	Ceiling speaker, 2-way-system, 10 watts, RAL 9010, metal, with thermal fuse and ceramic block, firedome, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPR/0233	81,20 \$
20102194	DL 20-200/T plus-EN54	Ceiling speaker, 2-way-system, 20 watts, RAL 9010, metal, with thermal fuse and ceramic block, firedome, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPR/0233	130,20 \$
20142904	DL-S 10-130/T plus-EN54	Ceiling speaker, 2-way-system, 10 watts (100V & 8ohms), RAL 9016, ABS, with thermal fuse, firedome certified EN 54-24, IP21C 1438/CPR /0431	200,20 \$
20142905	DL-E-AB 06-100/T-EN54 safe	Ceiling Speaker for AB-Cabling , 2x6 watts, RAL 9016, metal, with thermal fuse, ceramic block,certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPR/0347	61,60 \$
20102182	DL-AB 06-200/T-EN54	Ceiling Speaker for AB-Cabling , 2x6 watts, RAL 9010, metal, with thermal fuse, ceramic block, firedome, certified EN 54-24, BS5839 compliant, IP21C, 1438/CPR/0233	81,20 \$

20142910	DL-A-AB 06-100/T-EN54	Ceiling Speaker for AB-Cabling, surface-mount version, 2x6 watts, metal, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPR/0448	81,20 \$
20102195	DL-A 10-165/T-EN54	Ceiling speaker, surface-mounted version, 10 watts, RAL 9010, metal, with thermal fuse, ceramic block, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPD/0232	78,40 \$
20102196	DL-A 10-200/T-EN54	Ceiling speaker, surface-mounted version, 10 watts, RAL 9010, metal, with thermal fuse, ceramic block, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPD/0232	89,60 \$
20142881	DL-BR 15-130/T plus-EN54	Bassreflex-ceiling speaker, 2-way-system, 15 watts (100V & 8ohms), RAL 9016, ABS, with thermal fuse, certified EN 54-24, IP21C, 1438/CPR/0435	159,60 \$
20142882	DL-BR 30-165/T plus-EN54	Bassreflex-ceiling speaker, 2-way-system, 30 watts (100V & 8ohms), RAL 9016, ABS, with thermal fuse, certified EN 54-24, IP21C, 1438/CPR/0435	184,80 \$
			0,00 \$
20122605	DL-K 16-130/T-EN54	Sphere speaker, 16 watts, RAL 9010, ABS, with thermal fuse, ceramic block, certified EN 54-24, BS 5839 compliant, IP35, 1438/CPD/0325	103,60 \$
20122606	DL-K 20-165/T-EN54	Sphere speaker, 20 watts (100V & 8ohms), RAL 9010, ABS, with thermal fuse, ceramic block, certified EN 54-24, BS 5839 compliant, IP35, 1438/CPD/0325	172,20 \$
20142909	DL-RQ 10-165/T plus-EN54	Rectangular ceiling speaker, 2-way-system, 10 watts, ABS, RAL 9016, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPR/0440	86,80 \$
20122601	TS-C 10-300/T-EN54	Sound column outdoor, incl. swivel bracket, 10 watts, RAL 9006, aluminium, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP66, 1438/CPD/0315	116,20 \$
20122602	TS-C 20-500/T-EN54	Sound column outdoor, incl. swivel bracket, 20 watts, RAL 9006, aluminium, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP66, 1438/CPD/0315	155,40 \$
20122603	TS-C 30-700/T-EN54	Sound column outdoor, incl. swivel bracket, 30 watts, RAL 9006, aluminium, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP66, 1438/CPD/0315	193,20 \$
20122604	TS-C 50-1000/T-EN54	Sound column outdoor, incl. swivel bracket, 50 watts, RAL 9006, aluminium, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP66, 1438/CPD/0315	212,80 \$
20102197	WA 06-165/T-EN54	Wall speaker, soft-line, 6 watts, MDF, white, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP54, 1438/CPD/0231	60,20 \$
20102197V	WA 06-165/T-EN54V	Wall speaker, soft-line, 6 watts, MDF, white, with thermal fuse and ceramic block, ballproof, housing fixed by screws, certified EN 54-24, BS 5839 compliant, IP54, 1438/CPD/0231	71,40 \$
20102198	WA 06-165/T Metall-EN54	Wall speaker, 6 watts, RAL 9010, metal, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPD/0231	79,80 \$
20102183	WA-AB 06-100/T-EN54	Wall Speaker for AB-Cabling, 2x6 watts, white, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP54, 1438/CPD/0230	71,40 \$
20102183 V	WA-AB 06-100/T-EN54V	Wall Speaker for AB-Cabling, 2x6 watts, white, with thermal fuse and ceramic block, ballproof, fixed by screws, certified EN 54-24, BS 5839 compliant, IP54, 1438/CPD/0230	85,40 \$
20142913	WU-AB 06-100/T-EN54	Flush mounted speaker for AB-Cabling, 2x6 watts, ABS, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPR/0270	85,40 \$
20142911	WU 06-66/T-EN54	Flush mounted speaker , 6 watts, aluminium, with thermal fuse and ceramic block, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPR/0450	61,60 \$
20142912	WU-SW 06-165/T Metall-EN54	Baffle speaker, 6 watts, metal, black, with thermal fuse, certified EN 54-24, IP21C, 1438/CPR/0270	67,20 \$
20102245	WU 06-165/T-EN54	Flush mounted speaker, 6 watts, ABS, white, with plastic housing, thermal fuse, ceramic block, certified EN 54-24, BS 5839 compliant, IP21C, 1438/CPR/0270	72,80 \$
20122643	MS 15-100/T weiß-EN54	Monitor box, 2-way-system, swivel bracket included, 15 watts (100V & 8ohms), ABS, white, with thermal fuse, certified EN54-24, BS 5839 compliant, 1438/CPD/0348	64,40 \$
20122644	MS 15-100/T schwarz-EN54	Monitor box, 2-way-system, swivel bracket included, 15 watts (100V & 8ohms), ABS, black, with thermal fuse, certified EN54-24, BS 5839 compliant, 1438/CPD/0348	64,40 \$
20122645	MS 30-130/T weiß-EN54	Monitor box, 2-way-system, swivel bracket included, 30 watts (100V & 8ohms), ABS, white, with thermal fuse, certified EN54-24, BS 5839 compliant, 1438/CPD/0348	102,20 \$
20122646	MS 30-130/T schwarz-EN54	Monitor box, 2-way-system, swivel bracket included, 30 watts (100V & 8ohms), ABS, black, with thermal fuse, certified EN54-24, BS 5839 compliant, 1438/CPD/0348	102,20 \$
20122647	MS 50-165/T weiß-EN54	Monitor box, 2-way-system, swivel bracket included, 50 watts (100V & 8ohms), ABS, white with thermal fuse, certified EN54-24, BS 5839 compliant, 1438/CPD/0348	130,20 \$
20122648	MS 50-165/T schwarz-EN54	Monitor box, 2-way-system, swivel bracket included, 50 watts (100V & 8ohms), ABS, black, with thermal fuse, certified EN54-24, BS 5839 compliant, 1438/CPD/0348	130,20 \$
60609103	RAL-DA/-DA-S	Special colour in RAL - 4 digits colour scale (no pearl and metallic effect), for soundprojectors	36,40 \$
50617883	RAL-DL	Special colour in RAL - 4 digits colour scale (no pearl and metallic effect), for ceiling speakers	18,20 \$
32585198	RAL-TS-C	Special colour in RAL - 4 digits colour scale (no pearl and metallic effect), for sound columns	71,40 \$
60609123	RAL-WA/-WU	Special colour in RAL - 4 digits colour scale (no pearl and metallic effect), for wall- and flush-mounted speakers	25,20 \$
20163136	NCS-DL	Special colour in NCS colour scale, for ceiling speakers, 25 pcs. minimum order quantity	18,20 \$
20173262	DL-BR 165 IP	IP-Ceiling speaker, PoE capable, multicast, 2-way bassreflex, 8 watts, ABS, RAL 9010, supported protocols: TCP/IP, UDP, DHCP, IGMP	350,00 \$
20173272	MS 130 IP	IP-Monitor box, PoE capable, multicast, 2-way, 8 watts, ABS, white, supported protocols: TCP/IP, UDP, DHCP, IGMP	350,00 \$
20173404	IP-NAV	IP-Speaker Management Software for DL-BR 165 IP and MS 130 IP(compatible with WIN7, WIN8 and WIN10), license-key for 8 clients in one network	350,00 \$
20173361	M-IP	IP-Paging microphone, black, with LCD-display and integrated speaker, RJ45 connector, DC 24V	700,00 \$
20163042	DL-WIFI 60 plus	WiFi-Ceiling speaker, active 2-way-system, 2x30W, with power supply cable, controlled by ic audio app WIFI-Control 60,Android 5.0, IOS 9.0 or higher, sales only as a set of a pair, the price is the set-price	350,00 \$

61520130	DA-P 20-130/T	Soundprojector, 20 watts, ABS, white, IP56	53,20 \$
61416020	DA-S 20-130/T	Soundprojector, 20 watts, aluminium, RAL 9010, IP66	135,80 \$
71013000	DK 10/T	Horn speaker, 10 watts (100V & 20ohms), ABS (UL 94-V0), RAL 7035, IP66	65,80 \$
71516500	DK 15/T	Horn speaker, 15 watts (100V & 20ohms), ABS (UL 94-V0), RAL 7035, IP66	72,80 \$
73020000	DK 30/T	Horn speaker, 30 watts (100V & 20ohms), ABS (UL 94-V0), RAL 7035, IP66	86,80 \$
800125107	DK-MH 30/T plus	Music horn, 2-way-system, 30 watts, ABS, RAL 7035, IP66	218,40 \$
50617800	DL 06-130/T	Ceiling speaker, 6 watts, RAL 9010, metal, 180x98mm	22,40 \$
50622043	F 130	Metal fire dome for DL 06-130/T, RAL 9005	15,40 \$
50622000	DL 06-165/T	Ceiling speaker, 6 watts, RAL 9010, metal, 220x100mm	23,80 \$
50622030	DL 10-165/T	Ceiling speaker, 10 watts, RAL 9010, metal, 220x105mm	30,80 \$
50622018	F 165	Metal fire dome for DL 06-165/T, RAL 9005	15,40 \$
20071041	DL-E 06-165/T	Ceiling speaker, one-piece, 6 watts, RAL 9010, metal, 200x65mm	16,80 \$
20091425	FE 165	Metal fire dome for DL-E 06-165/T, RAL 9005	15,40 \$
51026000	DL 10-200/T	Ceiling speaker, 10 watts, RAL 9010, metal, 267x126mm	39,20 \$
51026021	F 200	Metal fire dome for DL 200-series, RAL 9005	30,80 \$
51277001	DL 06-66/T	Ceiling speaker, 6 watts, ABS, white, plastic, 100x83mm	22,40 \$
10222023	DL-P 06-100/T	Ceiling speaker, 6 watts, ABS (UL 94-HB), RAL 9010, plastic, IP44, 147x83mm	19,60 \$
10222025	DL-P 06-165/T	Ceiling speaker, 6 watts, ABS (UL 94-HB), RAL 9010, plastic, IP44, 210x80mm	23,80 \$
44624800	WA 06-165/T	Wall speaker, soft-line, 6 watts, MDF, white, IP54	30,80 \$
41613575	WA-LR 06-165/T	Wall speaker, incl. volume control, soft-line, 6 watts, MDF, white, IP54	40,60 \$
50617050	WA-LS-PE 06-165/T	Wall speaker, incl. volume control and priority relay, soft-line, 6 watts, MDF, white, IP54	54,60 \$
44624834	WA-BW 06-165/T	Wall speaker, soft-line, 6 watts, ABS, white, ball proof version, IP54	40,60 \$
20050599	WA 06-165/T	Metall Wall speaker, 6 watts, RAL 9010, metal	60,20 \$
20101847	MS active 165 weiß	Monitor box, active-system, mounting bracket included, 2x40 watts, ABS, white	148,40 \$
20101846	MS active 165 schwarz	Monitor box, active-system, mounting bracket included, 2x40 watts, ABS, black	148,40 \$